



| SERIES 525 | With Standard Shock | With MAX Shock |
|------------------------------|---------------------|-------------------|
| Diameter | 133 mm | 133 mm |
| Length w Safety Joint | 7.9 m | 10.5 m |
| Auto Activation Latch | Yes | Yes |
| Flow Rate Range | 900 – 1500 LPM | 900 – 1500 LPM |
| Frequency Range | 6 - 10 Hz | 6 – 10 Hz |
| Torsional Strength | 29,456 ft-lbs SP | 29,456 ft-lbs SP |
| Tensile Strength | 215,575 daN SP | 215,575 daN SP |
| Low Pressure Drop | 1,800 kPa | 1,800 kPa |
| Low Pressure Placement | 350 m | 700 m |
| Med Pressure Drop | 2,800 kPa | 2,800 kPa |
| Med Pressure Placement | 592 m | 1,255 m |
| High Pressure Drop | 4,000 kPa | 4,000 kPa |
| High Pressure Placement | 933 m | 1,881 m |
| SJ Length | 1.2 m | 1.2 m |
| Safety Joint ID | 57 mm | 57 mm |
| Make Up Torque Internal | 13 k – 18k ft-lbs | 13k – 18 k ft-lbs |
| Safety Joint Low Option | Break 50% MUT | Break 50% MUT |
| Safety Joint High Option | Break 70% MUT | Break 70% MUT |
| Shock, SlidePro + SJ Conn | DS40 | DS40 |
| Xover Options | XT39 CET43 | XT39 CET43 |